

## SOLID RESILIENT



- **Unique Tread Design** for improved traction and low rolling resistance.
- **3 - Stage construction** to deliver optimum performance, safety and comfort.
- **Super Solid Tyres** available in Premium, Standard and Budget versions.
- **Speciality Versions** include Non-Marking, Heat-Resistant, Cut-Resistant etc.
- **Available in Regular Base** and Limpet (Click / Lip) versions.



Tyre Size	Rim Size	Width (mm)	OD (mm)	Load Capacity (Kgs)	
				Load Wheel	Steer Wheel
4.00-8	3.75D-8	112	393	-	955
5.00-8	3.00D-8	102	450	-	877
15x41/2-8 (125/75-8)	3.00D-8	80	190	1040	800
16 x6-8 (150/75-8)	4.33R-8	113.5	190	1490	1150
18x7-8 (180/70-8)	4.33R-8	137	450	2145	1650
6.00-9	4.00E-9	123	520	1885	1390
21x8-9	6.00E-9	174	521	2755	2032
6.50-10	5.00F-10	144	562	2340	1800
23x9-10 (225/75-10)	6.50F-10	194	570	3160	2430
7.00-12	5.00S-12	157	647	2920	2182
23X10-12	8.00G-12	194	570	3160	2430
27X10-12	8.00G-12	196	520	2560	2890
8.25-15	6.50-15	212	761	4000	3000
750-15	6.50-15	188	736	3686	2568
700-15	5.50-15	190	693	3545	2597
28x9-15 (8.15-15)	7.00-15	198	510	2980	3100
250-15 (250/70-15)	7.00-15	205	726	4362	3157
300-15 (315/70-15)	8.00-15	246	809	5735	4333
9.00-20	6.50-20	215	790	3180	4000
10.00-20	8.00-20	222	990	5340	4450
12.00-20	8.00-20	270	1020	5840	4865